


# CONECTOR LIFE FIBER SC/UPC

SC/APC



## RELEVANT SOLUTIONS

- Easy operating, The connector can be directly used in ONU, also with fasten strength more than 5 kg, it is widely used in FTTH project of network revolution. It also reduce the use of sockets and adapters, save cost of project.
- With 86 standard socket and adapter, the connector makes connection between drop cable and patch cord. The 86 standard socket provides complete protection with its unique design.
- Applicable to connection with field mountable indoor cable, pigtail, patch cord and transformation of terminal box, distribution frame, ODF and patch cord.

## DESCRIPTION



1. Screw boot clamping.
2. Transparent side Cover, visible for Inspection.
3. Specific coating stripper/cutting guideway.
4. Suitable for narrow installation space.
5. Applicable to bow-type drop cable and 2.0/3.0 indoor cable.

Item	Parameter
Cable Scope	3.0 x 2.0 mm Bow-type Drop Cable 2.0/3.0 indoor cable
Fiber Diameter	125µm ( 652 & 657 )
Coating Diameter	250µm
Mode	SM
Operation Time	about 15s(exclude fiber presetting)
Insertion Loss	≤ 0.3dB (310nm & 1550nm)
Return Loss	≤ -50dB for UPC, ≤ -55dB for APC
Success Rate	>98%
Reusable Times	>10 times