

# LF CAJA EMP PREMIUM M2

48-96 F



## SPECIFICATION

Fiber Optic Splice Closure can be used in manhole, in handhole, aerial-hanger, wall-mounting, be directly buried and pedestal.



## DIMENSION

Height:53cm,  
Base diameter:16cm  
closet ring dia. :21cm  
4 small holes +1 oval hole  
The diameter of the small holes is 2.0cm.The major axis of the oval hole(inside wall) is 6.cm,and the shorter axis of the oval hole is 4.cm.  
Max. Fiber Capacity:  $24 \times 6 = 144$  fibers  
IP degree: IP 68  
Working temperature: 40 degree ~ 110 degree  
warranty: 25 years  
Materials: closure body: PP splice tray: ABS

## CONTENT OF FIBER OPTIC SPLICE CLOSURE

- |                           |                                  |
|---------------------------|----------------------------------|
| 1.Outer fixing part       | 8.Valve                          |
| 2.Clamp                   | 9.Shield continuity connector    |
| 3.Dome                    | 10.Sealing ring                  |
| 4.Base                    | 11.Inner fixing part             |
| 5.Splice tray             | 12.Strength member               |
| 6.Tray lid                | 13.Support ring on the base      |
| 7.Shield continuity wires | 14.Velcro strip with one X flake |

# LF CAJA EMP PREMIUM M2

48-96 F



## OVAL OUTLET CABLE SEAL KIT

- 1.Heat shrinkable sleeve
- 2.Aluminum cable protection tapes
- 3.Abrasive strip
- 4.Branch off clip



## CABLE SEAL KIT

- 1.Aluminum cable protection tape
- 2.Heat shrinkable sleeve
- 3.Abrasive strip

## OTHER ACCESSORIES

- 1.Desiccant
- 2.Shield continuity wires
- 3.Connector
- 4.Smouvs (splicing protection tubing)
- 5.transparent tubes Tie wraps

