

Power Meter T-OP300

- 1) Energy save mode
- 2) Built in VFL (optional)
- 3) Reference value storage



SPECIFICATIONS

Model	T-OP300T	T-OP300C
Measurement Range(dBm)	+10~-70dBm	+26~-50dBm
Accuracy *	± 0.2 dB	
Calibrated Wavelengths	850nm / 1300nm / 1310nm / 1490nm / 1550nm / 1625nm	
Resolution	0.01dB	
OPM Connector	2.5mm UPP and FC interchangeable (SC, ST optional)	
VFL Connector	2.5mm UPP	
Reference Value storage	Yes	
Auto Power Off	No operation in 10 minutes (can be canceled), Low battery	
Battery Charge	Yes	
Battery Life	Above 100 hours (1800mAH battery)	
Power Supply	AA * 2 batteries or AC/DC power supply adapter	
Size(H*W*D)	160mm *75mm * 32mm	
Weight	about 180g	
Operating Temperature	-10 -- +50 °C, < 90%RH	
Storage Temperature	-20 -- +60 °C, < 90%RH	

ACCESSORIES

Standard	Optional
Carrying bag*1	SC interchangeable connector*1
Calibration Certificate*1	ST interchangeable connector*1
User's manual*1	FC male to LC female adapter*1
	AC/DC adapter*1

* at 20±3°C, CW, with FC connector, -10dBm,

For 850nm, the Min. Power measurement: -60dBm@OP300T, -40dBm@OP300C